

Material Safety Data Sheet

Chromosulfuric Acid For Cleaning Glass Vessel(2.5 Ltrs Packing) (RXSOL-61-6397-205)



1. Product and Company Identification

Product Name Chromosulfuric Acid For Cleaning Glass Vessel(2.5 Ltrs Packing)

Product Type RXSOL-61-6397-205

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

2. Composition / information on ingredients

Chemical nature	Mixture of acids.
-----------------	-------------------

Substance: not applicable

Hazardous components (REGULATION (EC) No 1272/2008):

CAS-No.	Registration number	Classification
sulphuric acid ($\geq 50\%$ - $= 100\%$)		

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII:

7664-93-9	01-2119458838-20	Category 1, H290
	Skin corrosion	Category 1A, H314

chromium trioxide ($\geq 1\%$ - 2.5%) 1333-82-0 *):

Oxidising solid, Category 1	:H271
Carcinogenicity, Category 1A,	:H350
Germ cell mutagenicity, Category 1B	:H340
Reproductive toxicity, Category 2,	:H361f
Acute toxicity, Category 2	:H330
Acute toxicity, Category 3,	:H311
Acute toxicity, Category 3,	:H301
Specific target organ toxicity - repeated exposure, Category 1,	:H372
Skin corrosion, Category 1A,	:H314
Respiratory sensitisation, Category 1,	:H334
Skin sensitisation, Category 1	:H317
Acute aquatic toxicity, Category 1,	H400
Chronic aquatic toxicity, Category 1,	H410

A registration number is not available for this substance as the substance or its use are exempted from registration according to Article 2 REACH Regulation (EC) No 1907/2006, the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.

For the full text of the H-Statements mentioned in this Section, see Section 16.

**Hazardous components (1999/45/
Chemical Name (Concentration)**

CAS-No.	Classification
sulphuric acid	(>= 50 % - = 100 %)
7664-93-9 C,	Corrosive; R35

chromium trioxide (>= 1 % - 2.5 %)

1333-82-0 O, Oxidising;	R9
Carc.Cat.1;	R45
Mut.Cat.2;	R46
Repr.Cat.3;	R62
T+, Very toxic;	R26
T, Toxic;	R24/25-48/23
C, Corrosive;	R35/R42/43
N, Dangerous for the environment;	R50-53

For the full text of the R-phrases mentioned in this Section, see Section 16.

3. Hazards Identification

**Classification of the substance or mixture :
Classification (REGULATION (EC) No 1272/2008):**

Carcinogenicity, Category 1A,	:H350
Germ cell mutagenicity, Category 1B,	:H340
Acute toxicity, Category 4, Inhalation,	:H332
Skin corrosion, Category 1A,	:H314
Respiratory sensitisation, Category 1,	:H334
Skin sensitisation, Category 1,	:H317
Specific target organ toxicity - single exposure, Category 3,	:H335

Specific target organ toxicity - repeated exposure, Category 2,	:H373
Chronic aquatic toxicity, Category 3,	:H412

For the full text of the H-Statements mentioned in this Section, see Section 16: Classification (67/548/EEC or 1999/45/EC)

Carc.Cat.1 Carcinogenic Category 1	:R45
Mut.Cat.2 Mutagenic Category 2	:R46
T Toxic	:R23
C Corrosive	:R35
Xn Harmful	:R48/20
Sensitising	:R42/43
Dangerous for the environment	:R52/53

For the full text of the R-phrases mentioned in this Section, see Section 16: Label elements: Labelling (REGULATION (EC) No 1272/2008 Hazard pictograms: Signal word Danger

Hazard statements:

H350	May cause cancer.
H340	May cause genetic defects.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P201 Obtain special instructions before use.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P309 + P310 IF exposed or if you feel unwell: Immediately call a POISON CENTER or doctor/physician.

4. First Aid Measures

Description of first aid measures

General advice:

First aider needs to protect himself.

After inhalation: fresh air. If breathing stops: immediately apply artificial respiration, if necessary oxygen. Immediately call in physician. After skin contact: wash off with plenty of water. Immediately remove contaminated clothing. If available swab with polyethylene glycol 400. Call a physician immediately.

After eye contact:

rinse out with plenty of water. Immediately call in ophthalmologist. After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

Most important symptoms and effects, both acute and delayed:

Irritation and corrosion, Allergic reactions, Diarrhoea, Nausea, Vomiting Chromium(VI) is highly toxic. It is absorbed via both the lungs and the gastrointestinal tract. Being strong oxidisers, chromates/ bichromates can cause burns and ulcerations on the skin and mucous membranes and also irritations in the upper respiratory tract. Poorly healing ulcers occur after wound contact. In predisposed persons the substance rapidly leads to sensitisation and allergic reactions of the respiratory tract (risk of pneumonia!) and damage to nasal mucous membranes (under given circumstances perforation of the septum). After swallowing severe symptoms in the gastrointestinal tract such as bloody diarrhoea, vomiting (aspiration pneumonia!), spasms, circulatory collapse, unconsciousness, formation of methaemoglobin. Absorption may result in hepatic and renal damage. Inhalable chromium(VI) compounds gave clear evidence to be carcinogenic in animal experiments. Lethal dos(man): 0.5g. Antidotes: chelating agents such as EDTA, DMPS (Demaval®)

Indication of any immediate medical attention and special treatment needed: No information available.

5. Fire-fighting Measures

Extinguishing media:

Suitable extinguishing media:

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media:

Foam, Water

Special hazards arising from the substance or mixture:

Not combustible. Ambient fire may liberate hazardous vapours. The product reacts with water and generates heat. Fire may cause evolution of: Sulphur oxides.

Advice for firefighters:

Special protective equipment for firefighters Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing. Further information Suppress (knock down) gases/vapours/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Advice for non-emergency personnel: Avoid substance contact. Do not breathe vapours, aerosols. Ensure adequate ventilation. Evacuate the danger area, observe emergency

procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

Environmental precautions

Do not empty into drains.

Methods and materials for containment and cleaning up:

Cover drains. Collect, bind, and pump off spills.

Observe possible material restrictions (see sections 7 and 10).

Take up with liquid-absorbent and neutralising material (e.g. Chemizorb® H?, Merck Art. No. 101595). Dispose of properly. Clean up affected area.

Reference to other sections:

Indications about waste treatment see section 13.

7. Handling and Storage

Precautions for safe handling:

Advice on safe handling:

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Observe label precautions.

Hygiene measures:

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorised persons.

Storage temperature: no restrictions.

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

8. Exposure controls and personal protection

Control parameters

Components with workplace control parameters:

Basis	Value	Threshold limits	Remarks
-------	-------	------------------	---------

chromium trioxide (1333-82-0):

EH40 WEL	Time Weighted Average (TWA):	0.05 mg/m ³	Expressed as: as Cr
----------	------------------------------	------------------------	---------------------

Derived No Effect Level (DNEL)

sulphuric acid (7664-93-9):

Worker DNEL, acute	Local effects	inhalation	0.1 mg/m ³
Worker DNEL, longterm	Local effects	inhalation	0.05 mg/m ³

Recommended monitoring procedures:

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norms DIN EN 482 and DIN EN 689.

Predicted No Effect Concentration (PNEC)
sulphuric acid (7664-93-9)

PNEC Fresh water	0.0025 mg/l
PNEC Fresh water sediment	0.002 mg/kg
PNEC Marine water	0.00025 mg/l
PNEC Marine sediment	0.002 mg/kg
PNEC Sewage treatment plant	8.8 mg/l

Exposure controls:

Engineering measures:

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection

Tightly fitting safety goggles

Hand protection:

full contact: Glove material: Glove thickness: Break through time:	Viton (R) 0.70 mm > 480 min	
splash contact: Glove material: Glove thickness: Break through time:	Nitrile rubber 0.40 mm > 120 min	

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 890 Vitoject® (full contact), KCL 730 Camatril® -Velours (splash contact). The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet(>,>) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves

Other protective equipment

Acid-resistant protective clothing

Respiratory protection
required when vapours/aerosols are generated.

Recommended Filter type: Respirator.

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not empty into drains.

9. Physical and chemical properties

Information on basic physical and chemical properties:

Form	: Liquid
Colour	: Colourless.
Odour	Odour
Odour threshold	No information available.
pH	at 20 °C strongly acid
Melting point	No information available.
Boiling point	No information available.
Flash point	No information available.
Evaporation rate	No information available.
Flammability (solid, gas)	not applicable
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Vapour pressure	No information available.
Relative vapour density	No information available.
Relative density	1.84 g/cm ³ at 20 °C

Water solubility	at 20 °C soluble, (caution ! development of heat)
Partition coefficient: noctanol/ water	No information available.
Auto-ignition temperature	No information available.
Decomposition temperature	No information available.
Viscosity, dynamic	No information available.
Explosive properties	Not classified as explosive.
Oxidizing properties	Oxidising potential

Other data:

none

10. Stability and reactivity

Reactivity

See section 10.3

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

Violent reactions possible with:

alkalines

Risk of ignition or formation of inflammable gases or vapours with:

Acetone, halides

Light metals, Possible formation of:

Hydrogen

Exothermic reaction with:

Water, hydrochloric acid

Risk of explosion with:

organic combustible substances, highly flammable solvents, Impurities, acetic acid, Combustible Liquids

Conditions to avoid

Strong heating.

Incompatible materials

Aluminium, Copper, Copper alloys, Hydrogen may form upon contact with light metals (danger of explosion!).

Hazardous decomposition products
in the event of fire: See section 5.

11. Toxicological information

Information on toxicological effects:

Information on toxicological effects

Mixture

Acute oral toxicity:

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach., Nausea, Vomiting, Diarrhoea

Acute inhalation toxicity:

absorption

Symptoms: burns of mucous membranes, mucosal irritations, Cough, Shortness of breath, Lung oedema, Symptoms may be delayed., Possible damages:, damage of respiratory tract

Acute dermal toxicity:

This information is not available.

Skin irritation:

Mixture causes severe burns.

Eye irritation:

Mixture causes serious eye damage. Risk of blindness!

Sensitisation:

Mixture may cause allergy or asthma symptoms or breathing difficulties if inhaled.

Mixture may cause an allergic skin reaction.

Germ cell mutagenicity:

This information is not available.

Carcinogenicity:

This information is not available.

Reproductive toxicity:

This information is not available.

Teratogenicity:

This information is not available.

CMR effects

Carcinogenicity:

May cause cancer.

Mutagenicity:

May cause genetic defects.

Specific target organ toxicity - single exposure

Mixture may cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Mixture may cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

This information is not available.

11.2 Further information

Chromium(VI) is highly toxic. It is absorbed via both the lungs and the gastrointestinal tract.

Being strong oxidisers, chromates/ bichromates can cause burns and ulcerations on the skin and mucous membranes and also irritations in the upper respiratory tract. Poorly healing ulcers occur after wound contact. In predisposed persons the substance rapidly leads to sensitisation and allergic reactions of the respiratory tract (risk of pneumonia!) and damage to nasal mucous membranes (under given circumstances perforation of the septum). After swallowing severe symptoms in the gastrointestinal tract such as bloody diarrhoea, vomiting (aspiration pneumonia!), spasms, circulatory collapse, unconsciousness, formation of methaemoglobin.

Absorption may result in hepatic and renal damage. Inhalable chromium(VI) compounds gave clear evidence to be carcinogenic in animal experiments. Lethal dose (man): 0.5g. Antidotes: chelating agents such as EDTA, DMPS (Demaval®)

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Components

sulphuric acid

No information available.

chromium trioxide

Acute oral toxicity

LD50 rat: 50 mg/kg (IUCLED)

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.

Acute inhalation toxicity

LC50 rat: 0.217 mg/l; 4 h (IUCLID)

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

Acute dermal toxicity

LD50 rat: ca. 55 mg/kg (IUCLID)

Skin irritation

rabbit

Result: Causes burns.

(IUCLID)

Eye irritation

rabbit

Result: Causes burns.

(IUCLID)

Sensitisation

Patch test: human

Result: positive

(IUCLID)

Germ cell mutagenicity

Genotoxicity in vitro

Ames test

Result: positive

(IUCLID)

12. Ecological information

Toxicity

No information available.

Persistence and degradability

No information available.

Bioaccumulative potential

No information available.

Mobility in soil

No information available.

Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.

Other adverse effects

Additional ecological information

Biological effects:

Harmful effect due to pH shift.

Further information on ecology

Discharge into the environment must be avoided.

Components

sulphuric acid

Toxicity to daphnia and other aquatic invertebrates

EC50 Daphnia magna (Water flea): 29 mg/l; 24 h (IUCLID)

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.
chromium trioxide
Toxicity to daphnia and other aquatic invertebrates
EC50 Daphnia magna (Water flea): 0.162 mg/l; 48 h (ECOTOX Database)

13. Disposal considerations

Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

14. Transport information

Land transport (ADR/RID):

UN number	UN 2240
Proper shipping name	CHROMOSULPHURIC ACID
Class	8
Packing group	I
Environmentally hazardous	--
Special precautions for user	yes
Tunnel restriction code	E

Inland waterway transport (ADN):

Not relevant

Air transport (IATA):

UN number	UN 2240
Proper shipping name	CHROMOSULPHURIC ACID
Class	8
Packing group	I
Environmentally hazardous	--
14.6 Special precautions for user	no

Sea transport (IMDG):

UN number	UN 2240
Proper shipping name	CHROMOSULPHURIC ACID
Class	8
Packing group	I
Environmentally hazardous	--
Special precautions for user	yes

EmS F-A S-B

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations:

Major Accident Hazard

Legislation 96/82/EC
Toxic 2

Quantity 1: 50 t
Quantity 2: 200 t

Occupational restrictions Take note of Dir 94/33/EC on the protection of young people at work. Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers.

National legislation:

Storage class 6.1 D

Chemical Safety Assessment:

For this product a chemical safety assessment was not carried out.

16. Other information

Full text of H-Statements referred to under sections 2 and 3:

H271	May cause fire or explosion; strong oxidiser.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of R-phrases referred to under sections 2 and 3:

R 9	Explosive when mixed with combustible material.
R23	Toxic by inhalation.
R24/25	Toxic in contact with skin and if swallowed.
R26	Very toxic by inhalation.
R35	Causes severe burns.
R42/43	May cause sensitisation by inhalation and skin contact.
R45	May cause cancer.
R46	May cause heritable genetic damage.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R48/23	Toxic: danger of serious damage to health by prolonged exposure through inhalation.
R50	Very toxic to aquatic organisms.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53	May cause long-term adverse effects in the aquatic environment.
R62	Possible risk of impaired fertility.

Training advice:

Provide adequate information, instruction and training for operators.